

Floors – Permissible Loads - Gates

General:

Vehicles must not be driven in the exhibition hall B0 or the ICM Foyer.

Fork-lift trucks may only be used by the fair forwarding agent.

Passenger and freight elevators shall not under any circumstances be loaded beyond the permissible limits. The handling of freight in passenger elevators is prohibited. Damage caused by non-compliance with these rules shall be remedied by the ICM at the expense of the exhibitor or his agents.

	Hall B0	ICM Foyer
Length	65 m	
Width	54 m	
Total exhibition area	approx. 3 500 m ²	4600 m ² , depending on number of visitors
Clear height	Central area: 4.5 m Marginal area: 4.2 m	max. 12 m, min. 2.15 m
Floor	Oak timber parquet	Natural stone
Walls	Wood panelling	Stucco lustro panelling
Permissible floor load	2 t/m ² (20 kN/m ²)	1 t/m ² (10 kN/m ²)
Point load (on 30 x 30 cm)	8 t (80 kN)	2.1 t
Hall suspension points	100 kg (1 kN)	none
Entrance gate, (width x height)	12.50 m x 4.50 m	max. 3.00 m x 4.00 m above Foyer North
Entrance gates, number / doors	1, via gate 21	1, Foyer North, via gate 21
Illumination	400 Lux/m ²	daylight / 400 Lux/m ²
Ventilation system	partly air conditioned	fully air conditioned
Media supply	via utility ducts diagonal to hall longitudinal direction spacing 5 m, cross section (35 x 38 cm)	none / floor electronic grid, 9 x 6 m
Water connection, spacing 3 m	DN 25/3.5 bar	not possible
Drainage connection, spacing 3 m	DN 100	not possible
Connection facility for compressed air	DN 50/10 bar	not possible
Electricity supply	200 W/m ²	50 W/m ²
Telephone connections (wire line)	70	138
Telephone connections (mobile radio)	30	30
Telecom support points (floor/wall)	56	124
DP connections	112	149
Wideband communications connections	56	138